



NOTES:

1. THE APPLICABILITY OF THIS DETAIL TO A SPECIFIC SITE SHOULD BE VERIFIED BY THE APPROPRIATE REVIEW AGENCY AND/OR ENGINEER.
2. ROCK WALLS GREATER THAN 3' MEASURED FROM THE BOTTOM OF THE FOOTING TRENCH TO THE TOP OF THE WALL SHALL BE INDIVIDUALLY DESIGNED BY A CIVIL ENGINEER.
3. EXCAVATE A LEVEL TRENCH ALONG THE TOE OF THE SLOPE, TO INSTALL BASE AGGREGATE, PLACE LARGEST ROCK IN TRENCH WITH LONGITUDINAL AXIS PERPENDICULAR TO THE SLOPE FACE, BURY ROCK IN TRENCH DIAMETER OF ROCK.
4. ROCKS SHALL BE LAID WITH AT LEAST A THREE POINT BEARING ON PREVIOUSLY PLACED ROCK.
5. FOR NON-PERMITTED PROJECTS, REVEGETATE ADJACENT AREAS IN ACCORDANCE WITH THE TRPA BMP HANDBOOK. FOR PERMITTED PROJECTS, REVEGETATE ADJACENT AREAS TO SPECIFICATIONS OF REVEGETATION PLAN.

Stacked Rock Wall



BMP-205
November 2012